


2011 - IDS Conference Lightning Talk

Jon Jiras – Rochester Institute of Technology

Adding location, call number, and status availability to GIST Webpages in 3 easy steps:



Step 1

Create a PHP page that scrapes your catalog.

It does not have to be on ILLiad server.

We placed it on our library webserver.

```
<?php
$id = @$_GET['id'];
$url = "http://albert.rit.edu/search/i?SEARCH=$id";
$page = file_get_contents($url);
$dom = new DomDocument();
$dom->loadHTML($page);
$trs = $dom->getElementsByTagName("tr");
$str = '';
$output = array();
foreach($trs as $tr) {
    $attr = $tr->getAttribute("class");

    if ($attr == 'biblItemsEntry') {
        $str .= '<entry>';
        $tds = $tr->getElementsByTagName("td");
        $loc = $tds->item(0)->getElementsByTagName("a")->item(0)->nodeValue;
        $call = $tds->item(1)->getElementsByTagName("a")->item(0)->nodeValue;
        $status = $tds->item(2)->nodeValue;
        $status = substr($status, 2);
        $output[] = array('loc'=>$loc,'call'=>$call,'status'=>$status);
    }
}
echo "callbackfun(\"" . json_encode($output) . "\");";
```

URL to search your catalog by ISBN

ILS Specific Code – III
Pulls Location, Call Number, and Status

Encode the output as json and send it to a callbackfunction

Step 2

Add two functions to GIST.js

```
function customfunc() {  
    var isbn = document.getElementById("ISSN").value;  
    var url = "<script type='text/javascript' src='https://library.rit.edu/citationlinker/avail.php?id=" + isbn +  
    "?callback=callbackfun'></script>"  
    $('head').append(url);  
}  
  
}
```

Notice the URL includes a link to your php script and a javascript callback function

```
function callbackfun(json) {  
    var data = eval('(' + json + ')');  
    if (data.length < 1) exit;  
    var str = "<table style='table-layout:fixed;'>";  
    for (var i=0; i < data.length; i++) {  
        str += "<tr>";  
        str += "<td style='width:45%'>" + data[i].loc + "</td>";  
        str += "<td style='width:30%'>" + data[i].call + "</td>";  
        str += "<td style='width:25%'>" + data[i].status + "</td>";  
        str += "</tr>";  
    }  
}
```

Callback function parses the json and styles it

Step 3

Add a call to customfunc() in the existing wolrdcatData function of GIST.js

```
function worldcatData(mydata) { //WorldCat Data  
    [snip]  
    customfunc();  
}
```